

**Testo 510, Differential pressure meter, 130 hPa****Robust differential pressure gauge****The advantages at a glance**

- TopSafe (optional) protects from dust, dirt and impact
- One touch zero
- Hose connections for 4mm or 6.5mm inner diameter

**Example of use**

Tests  
pressure  
switches

*With testo 510 and TopSafe (optional), you have a robust, affordable differential pressure gauge with a measuring range up to 130 hPa.*

**Technical data - testo 510**

Storage temperature	-20.0...70.0 °C
Operation temperature	0.0...40.0 °C
Battery type	9V block battery
Battery life	150.0 h
Weight	0.0 g
Dimensions (BxLxH)	57.0 x 191.0 x 42.0 mm

Probe type (measuring value)	Measuring range		
Differential pressure probe (Pressure)	0.0 ... 130.0 hPa	Accuracy	+/-1.0% of f.v. (0.0 ... 130.0 hPa)
		Overload	+/-1300.0 hPa (0.0 ... 130.0 hPa)
		Resolution	+/-0.1 hPa (0.0 ... 130.0 hPa)
Differential pressure probe (Pressure)	0.0 ... 1300.0 mmH2O	Accuracy	+/-1.0% of f.v. (0.0 ... 1300.0 mmH2O)
		Overload	+/-13000.0 mmH2O (0.0 ... 1300.0 mmH2O)
		Resolution	+/-1.0 mmH2O (0.0 ... 1300.0 mmH2O)
Differential pressure probe (Pressure)	0.0 ... 100.0 mmHg	Resolution	+/-1000.0 mmHg (0.0 ... 100.0 mmHg) +/-1.0% (0.0 ... 100.0 mmHg) +/-0.1 mmHg (0.0 ... 100.0 mmHg)

UK / Europe / USA Office  
Tel: +44 (0)8700 434040  
Fax: +44 (0)8700 434045  
E-mails - [info@omniinstruments.co.uk](mailto:info@omniinstruments.co.uk)  
120-122 King Street ,Broughty Ferry,  
Dundee, Scotland UK. DD5 1EW

**Omni**  
**instruments**  
Measurement > Control > Data Acquisition  
Web Site: [www.omniinstruments.co.uk](http://www.omniinstruments.co.uk)

Australia / Asia Pacific Office  
Tel +61 (0)894 888 960  
Fax +61 (0)894 888 965  
[info@omniinstruments.com.au](mailto:info@omniinstruments.com.au)  
PO Box 105, Leederville  
Western Australia, 6902