

Testo 510, Differential pressure meter, 1.88 psi

Robust differential pressure meter in practical format

With testo 510 and TopSafe, you have a robust, affordable differential pressure gauge with a measuring range up to 1.88 psi.

The advantages at a glance

- TopSafe (optional) protects from dust, dirt and impact
- One touch zero
- Hose connections for 4mm or 6.5mm inner diameter



Technical data - testo 510

Storage temperature	-20.0...70.0 °C
Operation temperature	0.0...40.0 °C
Battery type	9V block battery
Battery life	150.0 h
Weight	0.0 g
Dimensions (BxLxH)	57.0 x 191.0 x 42.0 mm

Probe type (measuring value)	Measuring range		
Differential pressure probe (Pressure)	0.0 ... 1.88 psi	Accuracy	+/-1.0% of f.v. (0.0 ... 1.88 psi)
		Overload	+/-18.8 psi (0.0 ... 1.88 psi)
		Resolution	+/-0.0010 psi (0.0 ... 1.88 psi)
Differential pressure probe (Pressure)	0.0 ... 52.0 inH2O	Accuracy	+/-1.0% of f.v. (0.0 ... 52.0 inH2O)
		Overload	+/-520.0 inH2O (0.0 ... 52.0 inH2O)
		Resolution	+/-0.01 inH2O (0.0 ... 52.0 inH2O)
Differential pressure probe (Pressure)	0.0 ... 130.0 hPa	Accuracy	+/-1.0% of f.v. (0.0 ... 130.0 hPa)
		Overload	+/-1300.0 hPa (0.0 ... 130.0 hPa)
		Resolution	+/-0.1 hPa (0.0 ... 130.0 hPa)

UK / Europe / USA Office
 Tel: +44 (0)8700 434040
 Fax: +44 (0)8700 434045
 E-mails - info@omniinstruments.co.uk
 120-122 King Street ,Broughty Ferry,
 Dundee, Scotland UK. DD5 1EW

Omni
instruments
 Measurement > Control > Data Acquisition
 Web Site: www.omniinstruments.co.uk

Australia / Asia Pacific Office
 Tel +61 (0)894 888 960
 Fax +61 (0)894 888 965
info@omniinstruments.com.au
 PO Box 105, Leederville
 Western Australia, 6902