

# testo 608-H1



## Thermohygrometers for uninterrupted measurement

The accurate testo 608-H2 alarm hygrometer with an accuracy of  $\pm 2$  %RH and LED alarm function reliably warns you if limits have been exceeded.

### The advantages at a glance:

- With dew point calculation and max/min display
- Humidity sensor is not damaged by water saturation
- 18 s



Monitors ambient conditions and dew point in garden centres, storage and clean rooms, museums, laboratories. Stand-alone or attachable



Reliable monitoring of storage conditions in the food sector

Technical data - testo 608-H1	
Storage temperature	-40.0...70.0 °C
Operation temperature	0.0...50.0 °C
Battery type	9V block battery
Battery life	8736.0 h
Weight	168.0 g
Dimensions (BxLxH)	89.0 x 120.0 x 40.0 mm

Probe type (measuring value)	Measuring range		
Testo humid. sensor, cap. (Humidity)	10.0 ... 95.0 %rF	Accuracy	+/-3.0 %rF (10.0 ... 95.0 %rF)
		Resolution	+/-0.1 %rF (0.0 ... 100.0 %rF)
Testo humid. sensor, cap. (Humidity)	10.0 ... 95.0 %RH	Accuracy	+/-3.0 %RH (10.0 ... 95.0 %RH)
		Resolution	+/-0.1 %RH (0.0 ... 100.0 %RH)
NTC (Temperature)	0.0 ... 50.0 °C	Accuracy	+/-0.5 °C ( ... °C)
		Resolution	+/-0.1 °C (0.0 ... 50.0 °C)
Calc. parameter (Dew point)	-20.0 ... 50.0 °C td		

UK / Europe / USA Office  
 Tel: +44 (0)8700 434040  
 Fax: +44 (0)8700 434045  
 E-mails - [info@omniinstruments.co.uk](mailto:info@omniinstruments.co.uk)  
 120-122 King Street ,Broughty Ferry,  
 Dundee, Scotland UK. DD5 1EW

**Omni**  
**instruments**  
 Measurement > Control > Data Acquisition  
 Web Site: [www.omniinstruments.co.uk](http://www.omniinstruments.co.uk)

Australia / Asia Pacific Office  
 Tel +61 (0)894 888 960  
 Fax +61 (0)894 888 965  
[info@omniinstruments.com.au](mailto:info@omniinstruments.com.au)  
 PO Box 105, Leederville  
 Western Australia, 6902