

Testo 720



Pt100 laboratory thermometer

Testo 720 is resistant to corrosive substances when used with the indestructible TopSafe case.

The wide measuring range and accurate four wire technology make it an ideal instrument for everyday laboratory work.

The advantages at a glance :-

- Easy to read thanks to large display, 14mm character height
- With calibration protocol
- TopSafe with integrated bench stand



Examples of use

Technical data - testo 720	
Storage temperature	-20.0...70.0 °C
Operation temperature	0.0...50.0 °C
Battery type	Alkali manganese
Battery life	100.0 h
Weight	300.0 g
Dimensions (BxLxH)	57.0 x 190.0 x 42.0



Glass probe, the resistant alternative



Accurate temperature measurements in industry and laboratories

Probe type (measuring value)	Measuring range		
Pt100 (Temperature)	-100.0 ... 800.0 °C	Accuracy	+/-0.2 °C (-100.0 ... 199.9 °C) +/-0.2% of mv (200.0 ... 800.0 °C)
		Resolution	+/-0.1 °C (-100.0 ... 199.9 °C) +/-1.0 °C (200.0 ... 800.0 °C)
Pt100 (Temperature)	-150.0 ... 1470.0 °F	Accuracy	+/-0.2 °F (-150.0 ... 399.9 °F) +/-0.2% of mv (400.0 ... 1470.0 °F)
		Resolution	+/-0.1 °F (-150.0 ... 399.9 °F) +/-1.0 °F (400.0 ... 1470.0 °F)

UK / Europe / USA Office
Tel: +44 (0)8700 434040
Fax: +44 (0)8700 434045
E-mails - info@omniinstruments.co.uk
120-122 King Street ,Broughty Ferry,
Dundee, Scotland UK. DD5 1EW

Omni
instruments
Measurement > Control > Data Acquisition
Web Site: www.omniinstruments.co.uk

Australia / Asia Pacific Office
Tel +61 (0)894 888 960
Fax +61 (0)894 888 965
info@omniinstruments.com.au
PO Box 105, Leederville
Western Australia, 6902