

Testo 815 sound level meter, Class 3 L



Testo 815, an affordable sound level meter which meets the specifications of IEC 651/accuracy class 3 L.

The advantages at a glance

- Detachable microphone to avoid measurement errors
- Digital noise suppression for exact measurements
- Calibration via buttons
- Accurate quartz calibrator available as accessory



Measures office noise e.g. photocopiers, printers etc., accuracy class 3

Examples of use



Measures sound level of a disk saw, for example, accuracy class 3 L

Technical data - testo 815	
Storage temperature	-20.0...70.0 °C
Operation temperature	0.0...40.0 °C
Battery type	Alkali manganese
Battery life	15.0 h
Weight	170.0 g
Dimensions (BxLxH)	72.0 x 168.0 x 27.0 mm

Also available:-
Testo 815 Set,
accuracy class 3

Probe type (measuring value)	Measuring range		
Measuring microphone (Volume)	30.0 ... 130.0 dB(A)	Accuracy	+/-1.5 dB(A) (30.0 ... 130.0 dB(A))
		Resolution	+/-0.1 dB(A) (30.0 ... 130.0 dB(A))



UK / Europe / USA Office
Tel: +44 (0)8700 434040
Fax: +44 (0)8700 434045
E-mails - info@omniinstruments.co.uk
120-122 King Street ,Broughty Ferry,
Dundee, Scotland UK. DD5 1EW

Omni
instruments
Measurement > Control > Data Acquisition
Web Site: www.omniinstruments.co.uk

Australia / Asia Pacific Office
Tel +61 (0)894 888 960
Fax +61 (0)894 888 965
info@omniinstruments.com.au
PO Box 105, Leederville
Western Australia, 6902