

Testo 860-T3 infrared thermometer



Testo 860-T3 with its close focus (50:1) creates a 6mm wide spot at a distance of 0.3m.

The advantages at a glance

- Max/Min values
- Mean calculation/differential value
- Alarm function, audible and visual
- Freely adjustable emissivity from 0.10 to 1.00
- Materials table (preset emissivities)
- Internal data memory (100 pos.) with location management
- Data output RS 232 or analog output (1 mV/°C)
- Contact probe can be connected
- Mains connection
- Accurate spot sighting



Technical data - testo 860-T3	
Storage temperature	-20.0...50.0 °C
Operation temperature	0.0...50.0 °C
Operation humidity	10.0...95.0 %RH
Battery type	2 AA batteries
Battery life	10.0 h
Weight	480.0 g
Dimensions (BxLxH)	170.0 x 200.0 x 50.0 mm

Probe type (measuring value)	Measuring range		
Infrared (Temperature)	-30.0 ... 900.0 °C	Accuracy	+/-2.0 °C (-30.0 ... -5.0 °C) +/-0.75 °C (-4.9 ... 74.9 °C) +/-0.75% of mv (75.0 ... 900.0 °C)
		Resolution	+/-0.1 °C (-30.0 ... 900.0 °C)

Also available

Quicktemp 860-T3 set

Non-contact temperature measurement



UK / Europe / USA Office
 Tel: +44 (0)8700 434040
 Fax: +44 (0)8700 434045
 E-mails - info@omniinstruments.co.uk
 120-122 King Street ,Broughty Ferry,
 Dundee, Scotland UK. DD5 1EW

Omni
instruments
Measurement > Control > Data Acquisition
 Web Site: www.omniinstruments.co.uk

Australia / Asia Pacific Office
 Tel +61 (0)894 888 960
 Fax +61 (0)894 888 965
info@omniinstruments.com.au
 PO Box 105, Leederville
 Western Australia, 6902