


# **Transportation Probe**

Issue 4: 14th August 2009 (E&OE)

PBC-0002-3M




3000mm



## **Sensor Specification**

Measuring Range Sensor Type -40 °C to 125 °C (-40 °F to 257 °F) 10K NTC Thermistor

**Sensor Accuracy** 



40mm

## **Physical Specification**

IP Rating IP68 (waterproof)
Weight 90g

Response Time

Water 45 Seconds (to 90% FSD)

Sensor

Material TPE (Green)

Temperature rating -60 °C to 175 °C (-76 °F to 347 °F)

Cable

Material Silicon rubber

 $\begin{tabular}{ll} \textbf{Temperature rating} & -60\,^\circ\!\text{C to } +200\,^\circ\!\text{C } (-76\,^\circ\!\text{F to } +392\,^\circ\!\text{F}) \\ \end{tabular}$ 

Connector

Material L-104 (TPU)

Temperature rating -40 °C to 85 °C (-40 °F to 185 °F)

#### Notes

For specialist use, for example applications bringing the product into direct contact with food, we can supply material data sheets so you can assess the suitability of this product for your application.

34mm

#### Calibration

A UKAS traceable certificate of calibration can be supplied for an additional charge at the point of purchase.

## **Approvals**

Gemini Data Loggers (UK) Ltd. operates a Quality Management System which conforms to ISO 9001. The scope of the system covers the manufacture, design and supply of data loggers and their associated software, accessories and services.



## **Related Products**

This probe is suitable for use with the following products:

Tinytag Ultra 2 model numbers:

TGU-4020, TGU-4510

Tinytag Plus 2 model numbers:

TGP-4020, TGP-4510, TGP-4520

Tinytag View 2 model numbers:

TV-4020, TV-4510

