


# gSKIN<sup>®</sup> Heat Flux Sensors for R&D

- Ultra-high resolution of thermal energies and temperature differences
- Low invasiveness & thickness
- Versions with connectors compatible with all gSKIN<sup>®</sup> DLOG data loggers
- All sensors with conductive heat flux calibration cohering to ISO 8301



Product Name	gSKIN <sup>®</sup>		gSKIN <sup>®</sup>		gSKIN <sup>®</sup>		gSKIN <sup>®</sup>	gSKIN <sup>®</sup>
	XM 26 9C	XM 27 9C	XP 26 9C	XP 27 9C	XI 26 9C	XI 27 9C	XO 67 7C	XO-66 7C -Temp
Article Number	A-044336	A-044339	A-044573	A-044577	A-044628	A-044630	A-044717	A-044728
Detector Type	Thermoelectric		Thermoelectric		Thermoelectric		Thermoelectric	Thermoelectric / NTC
Surface Material (Sensing Area)	Anodized Aluminum		Anodized Aluminum		Anodized Aluminum		Polyamide	Polyamide
Sensing Dimensions (a x b x d) [mm x mm x mm]	4.4 x 4.4 x 0.5		10.0 x 10.0 x 0.5		18.0 x 18.0 x 0.5		30.0 x 30.0 x 3.3	30.0 x 30.0 x 3.3
Heat Flux Range Min / Max [kW/m <sup>2</sup> ]	-150 / 150		-150 / 150		-150 / 150		-15 / 15	-15 / 15
Noise Equivalent Heat Flux <sup>a</sup> [W/m <sup>2</sup> ] / absolute [μW]	0.34 / 6.6		0.05 / 5.0		0.02 / 4.6		0.07 / 64.3	0.07 / 64.3
Heat Flux Resolution [W/m <sup>2</sup> ] / absolute [μW] with gSKIN <sup>®</sup> DLOG <sup>b</sup>	0.41 / 7.9		0.06 / 6.1		0.02 / 5.7		0.09 / 78.4	0.09 / 78.4
Min./Avg. <sup>c</sup> Sensitivity (S) [μV/(W/m <sup>2</sup> )]	1.5 / 4.0		10.0 / 20.0		35.0 / 65.0		7.0 / 13.0	7.0 / 13.0
Temperature Dependence <sup>d</sup> of S [%/°C]	0.25		0.25		0.25		0.25	0.25
Response Time <sup>e</sup> (0-95%) [s]	0.7		0.7		0.7		n/a	n/a
Electrical Resistance [Ohm]	<20		<150		<400		<150	<150
Thermal Conductivity [W/(m <sup>2</sup> K)]	~1.1		~1.2		~1.3		~0.4	~0.4
Max. Compressive Force when clamped [kgf]	< 2		<10		<32		>32 (not specified)	>32 (not specified)
Operating Temperature Range Min/Max [°C]	-50 / 150		-50 / 150		-50 / 150		-50 / 80	-50 / 80
Calibration Temperature Range Min/Max [°C]	-30 / 70		-30 / 70		-30 / 70		-30 / 70	-30 / 70
Calibration Accuracy [±%]	3		3		3		3	3
Homogeneity <sup>f</sup> [±%]	1		1		1		1	1
Linearity with Power [±%]	1		1		1		1	1
Accuracy Temperature Measurement [°C]	n/a		n/a		n/a		n/a	+/- 0.2 (0-30 °C), +/- 0.4 (-20-60 °C)
Resolution Temperature Measurement [°C]	n/a		n/a		n/a		n/a	n/a
Flexprint Length (f) [cm]	5		5		5		n/a	n/a
Cable Length (c) [cm] (Connector, no/yes)	100 (no)	100 (yes)	100 (no)	100 (yes)	100 (no)	100 (yes)	100 (yes)	100 (no)

<sup>a</sup> Experimentally evaluated values under optimal steady state conditions.  
<sup>b</sup> Guaranteed minimum heat flux resolution using the gSKIN<sup>®</sup> DLOG-4219 (not applicable for XO-Temp)  
<sup>c</sup> Only a reference point.  
<sup>d</sup> The sensitivity increases (decreases) as the temperature goes above (below) 22.5 °C.  
<sup>e</sup> Refers to the heat flux measurement.  
<sup>f</sup> Conductive heat flux calibration cohering to the ISO8301 standard with mean temperature of 22.5 °C.  
<sup>g</sup> Position dependent signal change across sensing area.



For pricing or any further information, please contact Omni Instruments Ltd.