

Senturion XPD12 Proximity Probe



Applications

- Machine Shaft Position
- Turbine Differential Expansion
- Low profile mounting
- Harsh Environments

Features

- Switch selectable system cable lengths 5m, 7m and 9m.
- LED indication of selected length.
- 3.5mm socket for gap voltage monitoring.
- Double screened cable for high noise immunity.
- Snap lock and shake proof cable connection.
- Low profile driver for easy local integration to machine (Din rail mount opt).
- Excellent repeatability on replacement of probe, extension or driver.

The XPD12 proximity probe system consists of a calibrated probe, extension cable and driver. Utilising the eddy current principle, this combination forms a tuned circuit with the target material and variations in probe face to target distance are detected in this circuit by the driver. This provides a linearised voltage output proportional to target gap with a nominal sensitivity of 1.38 mV/um and a range of up to 12.0 mm. This type of measurement system provides highly accurate (resolution typically to a few micro-meters) relative positional measurements, for harsh environments up to 180 °C.

The driver unit offers selectable system lengths of 5 m, 7 m or 9 m, with a front panel green LED indicating the selected option. The gap voltage monitoring socket assists with commissioning the probe system; a volt meter can be connected directly to the driver through the 3.5 mm standard audio socket to display the gap voltage at the point of installation and the probe mechanical gap can then be adjusted to suite the application.

The cable system incorporates snap lock connectors which require no torqueing and provide a shake proof solution important for heavy industrial applications. The double screened cable offers robustness in combination with high immunity to interference and optional stainless steel convoluted armour is available for applications or environments where cable protection is paramount.

For pricing or any further information, please contact Omni Instruments Ltd.

System Performance


Measurement Range:	12.0 mm
Linear Range:	0.63 mm (25 mil) to 12.7 mm (500 mil) from electrical null position.
Electrical null position:	Approximately 0.50 mm from target (Driver at 0 V).
Linearity: (% of FS)	± 1%, -1.75 V to -17.5 V ± 2%, -1.0V to -17.5 V ± 2%, 0 °C to +150 °C @ -10.0V
Std Sensitivity:	1.38 V/mm (35 mV/mil) ± 1 %
Resolution:	<0.003 mm
Interchangability:	Maximum interchangability error replacing either probe, extension cable or driver in calibrated system is ± 5 %.
Available system lengths:	5 m, 7 m and 9 m
Cable length tolerance	
Probe (1 metre):	1.0 m to 1.5 m
Cable Extension (4 metre):	4.0 m to 4.4 m
Cable Extension (6 metre):	6.0 m to 6.6 m
Cable Extension (8 metre):	8.0 m to 8.8 m
Frequency Response:	DC to 5 kHz
Maximum Cable Length:	330 m based on 120 pF/m at <10 kHz and 500 um pk-pk. 3000 m based on 120 pF/m at <1 kHz and 500 um pk-pk.
Reference Target Material:	ANSI 4140

Probe


Probe tip diameter:	25.0 mm
Probe tip material:	PPS 40 % Glass Filled
Probe body material:	303 stainless steel
Probe body format:	Disk Type
Cable type:	Triaxial 75 Ohm Coaxial FEP outer jacket 3.2 mm outer diameter
Armoured option:	Convuluted Stainless Steel 6.4 mm outer diameter
Probe Resistance:	1.1 Ohms ± 0.2 Ohm With 1.0 m cable
Operating Temp Range:	-30 °C to +180 °C
Storage Temp Range:	-40 °C to +180 °C
Minimum target size:	2 x probe tip diameter
Magnetic field effect:	<1 % at 110 mT
Connector	Female Miniature Coaxial

Driver

Linear voltage range: Standard Option	-1.0 V to -17.5 V for 0.63 mm (25 mil) to 12.7 mm (500 mil)
System length selection:	Internal switch 5 m, 7 m or 9 m
System length indication:	Green LED lamp
Power supply range:	-16.0 Vdc to -28.0 Vdc Note: Output voltage is limited to 1.2 V below supply voltage when supply is < -21.5 V.
Power supply: sensitivity	< 0.3 mVout / Vsupply
Power consumption:	3 mA typ, 7 mA max
Output impedance:	75 Ohms
Monitor Output Impedance:	10 KOhm
Sensor Connector type:	Self Locking Miniature Male Coaxial
Monitor Connector type:	3.5 mm audio jack
Mounting:	Din Rail or Plate
Mass:	250 grams
Operating Temp Range:	-30 °C to +90 °C
Storage Temp Range:	-40 °C to +90 °C



Typical 5m system performance
 ————— 25 °C
 150 °C
 - - - - - 0 °C



Typical 5m system performance

Probe Ordering Information

XPD12 -

1.0 U 0 0

Cable length

- 1.0 = 1m
- 5.0 = 5m
- 7.0 = 7m
- 9.0 = 9m

Cable protection

- U = Unarmoured double screened (standard)
- C = Conduit (Convoluted SS)
- S = Heatshrink isolation over conduit
- G = M20 cable gland fitted to standard cable

Range (sensitivity)

0 = 0.63 - 12.7mm (0 - 500thou) (1.38mV/μm)

Intrinsic Safety

- 0 = None
- 1 = ATEX Ex II 1 G EEx ia IIC T4 (Tamb = -40°C to +180°C)

Driver Ordering Information

XED12 -

U 0 0

System length

- U = Universal Driver for 5m, 7m, and 9m systems
- S = Special requirements (2m, 12m, etc)

Range (sensitivity)

0 = 0.63 - 12.7mm (0 - 500thou) (1.38mV/μm)

Intrinsic Safety

- 0 = None
- 1 = ATEX Ex II 1 G EEx ia IIC T4 (Tamb = -40°C to +180°C)

Extension Cable Ordering Information

XEC -

4.0 U 0

Cable length

- 4.0 = 4m
- 6.0 = 6m
- 8.0 = 8m



Cable protection

- U = Unarmoured double screened (standard)
- C = Conduit (Convoluted SS)


Intrinsic Safety

- 0 = None
- 1 = ATEX Ex II 1 G EEx ia IIC T4 (Tamb = -40°C to +180°C)

Driver Mechanical Configuration




MOUNTING OPTIONS



TS35 RAIL


129.2

119.2




PANEL MOUNT (USING SUPPLIED CLIP)

Probe Mechanical Configuration



Extension Cable Mechanical Drawing



Whilst every effort has been made to ensure the accuracy of this specification, we cannot accept responsibility for damage, injury, loss or expense from errors or omissions. In the interest of technical improvement, this specification may be altered without notice.

For pricing or any further information, please contact Omni Instruments Ltd.