

## MX - FUEL AND OIL SERIES

	MX06F	MX09F	MX12F	MX19F	MX25F	MX40F	MX50F	MX75F	MX100F
--	-------	-------	-------	-------	-------	-------	-------	-------	--------

### CONSTRUCTION

<b>Meter Body</b>	Aluminium								
<b>Standard Rotors</b>	PPS	PPS	PPS	PPS	PPS	PPS	PPS	Alum	Alum
<b>Shafts</b>	316 Stainless Steel								
<b>Seals</b>	Viton								

### TECHNICAL SPECIFICATIONS

<b>Size</b>	¼"	½"	¾"	1"	1 ½"	2"	3"	4"	
<b>Flow Range (Litres)</b>	0.5-100 hr	15-500 hr	2-30 min	3-80 min	6-120 min	10-250 min	15-500 min	20-733 min	120-1200 min
<b>Max Pressure (PSI)</b>	1000	1000	2000	2000	2000	1200	1000	175	175
<b>Max Temperature</b>	80°C	80°C	80°C	80°C	80°C	80°C	80°C	80°C	80°C

### PROCESS CONNECTION

<b>BSP</b>	▪	▪	▪	▪	▪	▪	▪	▪	▪
<b>NPT</b>	▪	▪	▪	▪	▪	▪	▪	▪	▪
<b>ANSI</b>					▪	▪	▪	▪	▪
<b>DIN</b>					▪	▪	▪	▪	▪
<b>JIS</b>					▪	▪	▪	▪	▪

### PULSE OUTPUT

<b>Standard (reed/hall)</b>	▪	▪	▪	▪	▪	▪	▪	▪	▪
<b>Intrinsically Safe (Ex ia)</b>	<i>Only available with the <b>MX Industrial Process</b> series</i>								
<b>Flameproof (Ex d)</b>									
<b>High Temp (150°C)</b>									

### DISPLAYS

<b>PR (12mm digits)</b>	▪	▪	▪	▪	▪	▪	▪	▪	▪
<b>PRA (12mm c/w outputs)</b>	▪	▪	▪	▪	▪	▪	▪	▪	▪
<b>ER (17mm digits)</b>	▪	▪	▪	▪	▪	▪	▪	▪	▪
<b>ERA (17mm c/w outputs)</b>	▪	▪	▪	▪	▪	▪	▪	▪	▪
<b>ERB (Batch Controller)</b>	▪	▪	▪	▪	▪	▪	▪	▪	▪
<b>ERS (Net use function)</b>	<i>Remote mount only</i>								