

## MX - INDUSTRIAL SERIES

	MX06P	MX09P	MX12P	MX19P	MX25P	MX40P	MX50P	MX75P	
<b>CONSTRUCTION</b>	<b>Meter Body</b>	Stainless Steel							
	<b>Standard Rotors</b>	PPS	PPS	PPS	PPS	PPS	PPS	PPS	ALUM
	<b>High Visc. Rotors</b>	316 Stainless Steel							
	<b>High Temp Rotors</b>	316 Stainless Steel							
	<b>Shafts</b>	316 Stainless Steel							
	<b>Seal</b>	FEP (Teflon Encapsulated)							
<b>TECHNICAL SPECIFICATIONS</b>	<b>Size</b>	¼"	¼"	½"	¾"	1"	1 ½"	2"	3"
	<b>Flow Rate</b> (Litres)	0.5-100 hr	15-500 hr	2-30 min	3-80 min	6-120 min	10-250 min	15-500 min	20-733 min
	<b>Max Pressure</b> (PSI)	1000	1000	2000	2000	2000	1500	1200	175
	<b>Max Temperature</b>	150°C	150°C	150°C	150°C	150°C	150°C	150°C	120°C
<b>PROCESS CONNECTION</b>	<b>BSP</b>	▪	▪	▪	▪	▪	▪	▪	▪
	<b>NPT</b>	▪	▪	▪	▪	▪	▪	▪	▪
	<b>ANSI</b>					▪	▪	▪	▪
	<b>DIN</b>					▪	▪	▪	▪
	<b>JIS</b>					▪	▪	▪	▪
<b>PULSE OUTPUT</b>	<b>Standard</b> (Reed/Hall)	▪	▪	▪	▪	▪	▪	▪	▪
	<b>Intrinsically Safe</b> (Ex ia)	▪	▪	▪	▪	▪	▪	▪	▪
	<b>Flameproof</b> (Exd)	▪	▪	▪	▪	▪	▪	▪	▪
	<b>High Temp</b> (150°C)	<i>only available with the High Visc and High Temp Rotor option</i>							
<b>DISPLAYS</b>	<b>PR</b> (12mm digits)	▪	▪	▪	▪	▪	▪	▪	▪
	<b>PRA</b> (12mm c/w outputs)	▪	▪	▪	▪	▪	▪	▪	▪
	<b>ER</b> (17mm digits)	•	•	▪	▪	▪	▪	▪	▪
	<b>ERA</b> (17mm c/w outputs)	•	•	▪	▪	▪	▪	▪	▪
	<b>ERB</b> (Batch Controller)	▪	•	▪	▪	▪	▪	▪	▪
	<b>ERS</b> (Net use function)	<i>Remote mount only</i>							