

gSKIN® KIT Heat Flux Kit

FEATURES

- Calibrated Plug-and-Play solution
- Get ready-to-use heat flux data with a resolution < 0.41 W/m²
- Logger and live read-out
- Stores up to 2 million data points
- Read-out software included
- USB interface
- For scientific and analytical measurements



gSKIN®-XB 27 9C



DLOG-4219



MOUNT-1211

Product Name	gSKIN® KIT-1583C
Article Number	A-061895
gSKIN® KIT includes ^a	Sensor: gSKIN®-XB 27 9C (4.4mm x 4.4mm) Logger: DLOG-4219 Mounting Tape: MOUNT-1211
Sensor Calibration	Method cohering to ISO8301, mean temperature of 22.5°C
Min. Heat Flux Range [W/m ²]	±550
Heat Flux Resolution [W/m ²]	<0.41
Min. Sensor Sensitivity ^b (S) [µV/(W/m ²)]	1.5
Response Time (0-95%) [s]	0.2 ^c / 0.7
Logger Dimensions (l x w x h) [mm x mm x mm]	52 x 20 x 15
Measurement Frequency	50/s to 2/d
Bit Resolution [bits]	12
Data Storage Capacity [# measurements]	>2'000'000
Battery Lifetime ^d [days]	>30 (rechargeable)
Computer Interface	USB
Software	Installation CD included
Operating System	Windows 2000 / XP / Vista / 7 / 8
Operation Modes	Autonomous / Button Triggered / Live
Operating Temperature Range Min/Max [°C]	-50 / 150 (-25 / 65 for Logger)
Calibration Temperature Range Min/Max [°C]	-30 / 70
Calibration Accuracy ^b [±%]	3
Sensor / Logger Cable Length [m]	1.0 / 0.5 (with connectors)

^a For more details consult the datasheets of the individual products.

^b Sensor calibration data already loaded onto logger for simple and fast plug-and-play measurements.

^c Anticipated.

^d At lowest measurement frequency (2/d).

Datasheet V4.7, © Copyright greenTEG AG, 2014 All Rights Reserved

Whilst every effort has been made to ensure the accuracy of this specification, we cannot accept responsibility for damage, injury, loss or expense from errors or omissions. In the interest of technical improvement, this specification may be altered without notice.

For pricing or any further information, please contact Omni Instruments Ltd.