

General purpose, top-entry velocity transducer with DC output. Made from robust stainless steel throughout for continuous vibration monitoring in harsh environments. Sealed to IP67 with industry standard two-wire 4-20mA output proportional to sensor range that can connect directly to PLC, DCS and other industrial controllers. Includes integral stainless overbraided ETFE cable and is available with a wide range of mountings.

MTN/1185C



Applications

- Air handling units
- Building services
- Fans

Technical

Output current 4-20mA DC proportional to rms velocity (mm/s)

Supply voltage 12-32V DC (4-20mA)

Frequency response 2Hz to 1kHz $\pm 10\%$

Mounted base resonance 5kHz (nominal)

Isolation Base isolated

Dynamic range 50g peak

Transverse sensitivity Less than 5%

Operating temperature -25 to 90°C

Temperature sensitivity 0.08%/°C

Case material Stainless steel

Cable Integral stainless steel overbraided ETFE

Standard cable length 5m


Maximum cable length 100m

Mounting torque 8Nm

Weight 150g (nominal)

Sealing IP67

Dimensions




For pricing or any further information, please contact Omni Instruments Ltd.

Studs and grub screws



Part #	From	To
MS036	¼"-28 UNF Male	M6 Male
MS039	¼"-28 UNF Male	10-32 UNF Male
MS067	¼"-28 UNF Male	M8 Male
MS068	¼"-28 UNF Male	¼"-28 UNF Male
MS124	¼"-28 UNF Male	M10 Male
MS132	¼"-28 UNF Male	M12 Male

Quick fit adapters




Part #	From	To
MS001	Q/F Male	Glue base
MS002	Q/F Male	M8 Male
MS003	Q/F Male	M10 Male
MS004	Q/F Male	¼"-28 UNF Male
MS006	Q/F Male	M6 Male

Options

- Connector
- Filters
- Mounting threads
- Other velocities (see below)

Part #	Mounting	xx = Optional Velocity (mm/s rms)
MTN/1185C-xx	¼" UNF Female	0-10
MTN/1185CQ-xx	Q/F Female	0-20
		0-25
		0-50
MTN/1185NPTC-xx	½" NPT Male	0-100

Mounting adapters




Part #	From	To
MS005	Q/F Male	¼"-28 UNF Female
MS007	Q/F Male	10-32 UNF Female
MS008	Q/F Male	M8 Female
MS011	¼"-28 UNF Male	Q/F Female
MS013	¼"-28 UNF Male	Glue base
MS033	¼"-28 UNF Male	Q/F Female
MS038	Q/F Male	M8 Conical Male
MS061	¼"-28 UNF Male	10-32 UNF Male
MS079	¼"-28 UNF Male	Q/F Female
MS106	Q/F Male	M10 Female

Isolation

Part #	From	To
MS034	¼"-28 UNF Male	¼"-28 UNF Female
MS093	Q/F Male	M8 Male

System connection



For pricing or any further information, please contact Omni Instruments Ltd.