

Multifunctional TFT Wind Display

Wind Speed Indicator & Wind Display

Key Features

- Digital output
- 2/10 min & user average
- Wind variation
- Maximum gust
- Meteorological or Marine display modes
- Knots, m/s, mph, km/h & Beaufort
- Optional auto/manual brightness control
- Resolution WVGA 800x480

The Multifunctional TFT Wind Display can display wind speed and direction in either meteorological (N-E-S-W) or marine (port/starboard) mode. Wind information is displayed using 8.5" LED backlight, industrial grade LCD screen and the data will be indicated with a true viewing angel of 170°

The Multifunctional TFT Wind Display receives data directly from the wind sensor in NMEA mode without the need for additional interfaces. It provides the power supply for the wind sensor and can be "daisy chained" to a second wind display to transfer wind sensor information.

Also suitable for 144x144 mm instrument replacement (portrait or landscape)¹



DISPLAY

Speed display	Central, 3 digit, 11mm height
Gust display	3 digit, 8mm height
Average	2 minutes, 10 minutes, User defined
Other	Wind Variance

WIND SPEED

Units	mph, m/s, knots, km/h, Beaufort
-------	---------------------------------

DIRECTION

Direction display	Left hand side, 3 digit, 8mm height
Direction average	Grey arrow indicator on the display and value in the direction display

INPUT /OUTPUT

Input	NMEA (output from Gill anemometer)
Output	+15 VDC Sensor supply RS422 daisy chain output
Formats	NMEA 4800 Baud

POWER REQUIREMENT

Power supply	100 to 240 Vac, 50/60 Hz, max 50 VA. Option for 18-32Vdc
--------------	---

MECHANICAL

Size	238 x 148.5 x 71mm
Weight	1.2kg

ENVIRONMENTAL

Humidity	10% to 93% RH
Operational Temperature	-15°C to +55°C
Moisture Protection	IP22
EMC	ESD IEC 61000-4-2 Radiated Immunity IEC 61000-4-3 Conducted Immunity IEC 61000-4-6 Fast Transients IEC 61000-4-4 Surge IEC 61000-4-5

Typical Applications

- Marine
- Meteorological/Hydrological
- Aviation/Industrial/Transport/Construction

Whilst every effort has been made to ensure the accuracy of this specification, we cannot accept responsibility for damage, injury, loss or expense from errors or omissions. In the interest of technical improvement, this specification may be altered without notice.

For pricing or any further information, please contact Omni Instruments Ltd.