

Series PD-33X

Piezoresistive differential pressure transmitters with excellent accuracy

Features

- RS485 interface can be combined with analog interface
- Analog interface rangeable by RS485 interface (turn-down)
- Modbus RTU protocol for process values and configuration
- Line pressure up to 600 bar
- Excellent long-term stability



Technology

- Insulated and encapsulated piezoresistive pressure sensor (classic "wet-wet")
- High-quality differential pressure transducers and tried-and-tested mathematical compensation

Typical applications

- Filter monitoring
- Flow rate measurement
- Leakage measurement
- Laboratory use
- Industrial applications

Accuracy

± 0,05 %FS

Total error band


± 0,1 %FS @ -10...80 °C

Pressure ranges

0...0,3 to 0...30 bar



Series PD-33 X



For pricing or any further information, please contact Omni Instruments Ltd.

Contact Details:

Tel: +44 1382 443000

Email: info@omni.uk.com

Website: www.omniinstruments.co.uk

Mailing Address:

Unit 1, 14 Nobel Road,
Wester Gourdie Industrial Estate,
Dundee, DD2 4UH.

Series PD-33X – specifications

Standard pressure ranges

Differential pressure PD		Positive proof pressure	Negative proof pressure
0...0,3	-0,3...0,3	5	2,5
0...1	-1...0	15	7,5
	-1...1		
0...3			
0...6		50	25
0...10			
0...16			
0...30		120	60
bar diff.		bar	
Reference pressure at 0 bar differential pressure		Based on reference pressure	

Note:

all intermediate ranges for the analog interface possible from the standard ranges by scaling (turn-down) at no extra charge. Smallest range: 0,1 bar
Also negative and further +/- ranges possible. Optional: adjustment directly at intermediate ranges

Performance

Pressure

Digital nonlinearity	$\leq \pm 0,02$ %FS	Best fitted straight line (BFSL)
Accuracy @ RT (20...25 °C)	$\leq \pm 0,05$ %FS	Nonlinearity (best fitted straight line BFSL), pressure hysteresis, non-repeatability, zero point deviation and amplification deviation
Total Error Band (10...40 °C)	$\leq \pm 0,05$ %FS	Max. deviation within the compensated pressure and temperature range.
Total Error Band (-10...80 °C)	$\leq \pm 0,1$ %FS	Max. deviation within the compensated pressure and temperature range. Experience shows that, outside the compensated temperature range, the total error band in the ambient temperature range is expanded by 0,1 %FS.
Compensated temperature range	10...40 °C	Extended temperature range RT.
	-10...80 °C	Other optional temperature ranges within -40...125 °C possible.
Note	The compensated temperature ranges with the corresponding total error band are ordering options.	
Analog interface additional deviation	$\leq \pm 0,05$ %FS	With reference to accuracy @ RT and the Total Error Band.
Long-term stability	$\leq \pm 0,1$ %FS	Per year under reference conditions, yearly recalibration recommended.
Line pressure	≤ 200 bar	Either, see Dimensions & options
	≤ 600 bar	
Line pressure dependency	$< 0,005$ %FS/bar	For pressure ranges ≥ 3 bar
	$< 0,15$ mbar/bar	For pressure ranges < 3 bar
Position dependency	$\leq \pm 3$ mbar	Calibrated with horizontal positioning of the pressure connections.
Resolution	0,0005 %FS	Digital
Signal stability	0,0025 %FS	Digital noise-free
Internal measurement rate	≥ 1800 Hz	For version «3-wire + digital (0...10 V. 0...5 V)» > 6000 Hz
Pressure range reserve	± 10 %	Outside the pressure range reserve, +Inf / -Inf is displayed If there is an error in the device, NaN is displayed.
Note	For pressure ranges < 1 bar, all data apply with reference to a full-range signal (FS) of 1 bar.	

Temperature

Accuracy	$\leq \pm 2$ °C	The temperature is measured on the pressure sensor (silicon chip) that sits behind the metallic separating diaphragm. The data apply within the compensated temperature range.
Resolution	$\leq 0,01$ °C	
Internal measurement rate	> 10 Hz	

For pricing or any further information, please contact Omni Instruments Ltd.

Series PD-33X – specifications

Electrical data

Connectivity	digital	2-wire + digital	3-wire + digital		
Analog interface		4...20 mA	0...10 V	0...5 V	0,1...2,5 V
Digital interface	RS485	RS485	RS485	RS485	RS485
Power supply	3,2...32 VDC	8...32 VDC	13...32 VDC	8...32 VDC	3,2...32 VDC
Power consumption (without communication)	< 8 mA	3,5...22,5 mA	< 8 mA	< 8 mA	< 8 mA
RS485 voltage insulation	± 32 VDC	± 18 VDC	± 32 VDC	± 32 VDC	± 32 VDC
Note	Disturbance of the 4...20 mA signal occurs during communication through the digital interface. 3-wire types are suitable for simultaneous operation of the analog and digital interface.				

Start-up time (power supply ON)	< 250 ms
Overvoltage protection and reverse polarity	± 32 VDC
GND case insulation	> 10 MΩ @ 300 VDC

Analog interface

Load resistance	< (U - 8 V) / 25 mA	2-wire
	> 5 kΩ	3-wire
Limiting frequency	≥ 300 Hz	2-wire
		3-wire (0,1...2,5 V)
	≥ 1000 Hz	3-wire (0...10 V, 0...5 V)
Note	Filter properties can be adjusted by the customer	

Digital interface

Type	RS485	Half-duplex
Communication protocols	Modbus RTU	
	KELLER bus protocol	Proprietary
Identification	Class.Group: 5.24	
Unit of pressure	bar	Standard settings: bus address 1, baud rate 9600 bit/s
Unit of temperature	°C	
Data type	Float32 and Int32	Other default settings available on request. Can be reconfigured via software by the customer later.
Baud rates	9600 and 115'200 bit/s	
Lines	up to 1,2 km	

Electrical connection

Plug	Round plug 423 - 723 - 425	M16 x 0,75	DIN EN 61076-2-106, 5-pole
	Round plug	M12 x 1	DIN EN 61076-2-101, A-coded, 5-pole
	Bayonet connector	Souriau Serie 8525	MIL-STD-1669, 5-pole
	Valve connector (without RS485)	Form A (18 mm)	DIN EN 175301-803-A (DIN 43650)
Cable	ø 5,8 mm, PE sheath	5-wire, cable gland	

Electromagnetic compatibility

CE conformity as per 2014/30/EU (EMC)	EN IEC 61326-1 / EN IEC 61326-2-3 / EN IEC 61000-6-1 / EN IEC 61000-6-2 / EN IEC 61000-6-3 / EN IEC 61000-6-4
---------------------------------------	---

For pricing or any further information, please contact Omni Instruments Ltd.

Series PD-33X – specifications

Mechanical data

Wetted parts

Pressure connection	Stainless steel AISI 316L	
Pressure transducer separating diaphragm	Stainless steel AISI 316L	
Pressure transducer seal (internal)	FKM	others on request
Pressure connection seal (external)	none	

Other materials

Pressure transducer oil filling	Silicone oil	others on request
---------------------------------	--------------	-------------------

Further details

Pressure connection	G1/4 female	See Dimensions and options
	1/4-18NPT female	
Width x height	59 mm x approx. 120 mm	
Weight	approx. 500 g	Line pressure 200 bar
	approx. 650 g	Line pressure 600 bar



Ambient conditions


Media temperature range	-20...125 °C	Optional -40...125 °C	Icing not permitted
Ambient temperature range	-20...85 °C	Optional -40...85 °C	
Storage temperature range	-20...85 °C		
Protection	IP67	Round plug 423 - 723 - 425, M16 x 0.75	
	IP65	Valve plug, form A, DIN EN175301-803-A (formerly DIN 43650)	
	IP65	Bayonet connector, Souriau series 8525	
	IP67	Round plug, M12 x 1	
	IP68	Cable gland	
Notes	Degrees of protection are valid with the corresponding mating plug in mated condition.		
Vibration resistance	10 g, 10...2000 Hz, ± 10 mm	IEC 60068-2-6	
Shock resistance	50 g, 11 ms	IEC 60068-2-27	
Pressure endurance @ RT (20...25 °C)	> 10 million pressure cycles	0...100 %FS	


For pricing or any further information, please contact Omni Instruments Ltd.



Series PD-33X – Dimensions and options


Electrical connections





Round plug 423 - 723 - 425	2-wire		3-wire	
M16 x 0,75	4...20 mA		0...max. 10 V	
	1	OUT/GND	1	GND
	2	n.c.	2	+OUT
	3	+Vs	3	+Vs
	4	RS485A	4	RS485A
	5	RS485B	5	RS485B


Round plug	2-wire		3-wire	
M12 x 1	4...20 mA		0...max. 10 V	
	1	OUT/GND	1	GND
	2	n.c.	2	+OUT
	3	+Vs	3	+Vs
	4	RS485A	4	RS485A
	5	RS485B	5	RS485B



Cable gland	2-wire		3-wire	
Cable ø 5,8	4...20 mA		0...max. 10 V	
	WH	OUT/GND	WH	GND
	RD	n.c.	RD	+OUT
	BK	+Vs	BK	+Vs
	BU	RS485A	BU	RS485A
	YE	RS485B	YE	RS485B
	Shield on CASE		Shield on CASE	

Valve plug	2-wire		3-wire	
Form A	4...20 mA		0...max. 10 V	
	1	OUT/GND	1	GND
	2	n.c.	2	+OUT
	3	+Vs	3	+Vs
	⬇	CASE	⬇	CASE





Bayonet connector	2-wire		3-wire	
Souriau Serie 8525	4...20 mA		0...max. 10 V	
	C	OUT/GND	C	GND
	B	n.c.	B	+OUT
	A	+Vs	A	+Vs
	D	RS485A	D	RS485A
	F	RS485B	F	RS485B
	Shield on CASE		Shield on CASE	

For pricing or any further information, please contact Omni Instruments Ltd.



Series PD-33X – Dimensions and options

Available pressure connections

For line pressure ≤ 200 bar

G1/4 female	1/4-18NPT female
 <p>Technical drawing of the G1/4 female connection for ISO 228-1. The drawing shows a cross-section of the pressure transmitter with dimensions: top diameter $\varnothing 25,05$, total height 24, mounting hole diameter $\varnothing 30$, and mounting hole spacing 58,7. The connection is G1/4 female.</p>	 <p>Technical drawing of the 1/4-18NPT female connection for ISO 228-1. The drawing shows a cross-section of the pressure transmitter with dimensions: top diameter $\varnothing 25,05$, total height 24, mounting hole diameter $\varnothing 30$, and mounting hole spacing 58,7. The connection is 1/4-18NPT female.</p>
ISO 228-1	ISO 228-1

For line pressure ≤ 600 bar

G1/4 female	1/4-18NPT female
 <p>Technical drawing of the G1/4 female connection for ISO 228-1. The drawing shows a cross-section of the pressure transmitter with dimensions: top diameter $\varnothing 25,05$, total height 5, mounting hole diameter $\varnothing 4,0$, and mounting hole spacing 59. The connection is G1/4 female.</p>	 <p>Technical drawing of the 1/4-18NPT female connection for ISO 228-1. The drawing shows a cross-section of the pressure transmitter with dimensions: top diameter $\varnothing 25,05$, total height 5, mounting hole diameter $\varnothing 4,0$, and mounting hole spacing 59. The connection is 1/4-18NPT female.</p>
ISO 228-1	ISO 228-1

Other customer-specific options

- Other compensated pressure ranges
- Other compensated temperature ranges within $-40 \dots 125$ °C are possible
- Other electrical connections
- O-Ring made of other materials
- Version without internal seals
- Other oil filling types for pressure transducers
- Integration of application-specific calculations
- Modifications to customer-specific options

Examples of related products

- Series PD-33Xc: Differential pressure transmitters with highest accuracy and CANopen interface
- Series 33X: Pressure transmitters with excellent accuracy 0,01 %FS
- Series 35X: Pressure transmitters with front-flush metal diaphragm and highest accuracy
- Series PD-23X: Differential pressure transmitters with high accuracy
- OEM series: Pressure transducers with electronics (e.g. series PD-10LX) for integration in one's own systems

For pricing or any further information, please contact Omni Instruments Ltd.

Series PD-33X – Software, scope of delivery and accessories

Modbus interface

The X-line products have a digital interface (RS485 half-duplex), which supports the MODBUS RTU and KELLER bus protocols. Details of the communication protocols can be found at www.keller-druck.com. Documentation, a Dynamic Link Library (DLL) and various programming examples are available for integrating the communication protocol into your own software.

Interface converters

The connection to a computer is established via an RS485-USB interface converter. To ensure smooth operation, we recommend the K-114 with the corresponding mating plug, robust driver module, fast RX/TX switching and connectable bias and terminating resistors.

"CCS30" software

The licence-free CCS30 software is used to carry out configurations and record measured values.

Measurement collection

- Live visualisation
- Adjustable measuring and storage interval
- Export function
- Parallel recording in bus operation
- Up to 100 measured values per second




Configuration

- Call up of information (pressure and temperature range, software version, serial number etc.)
- Readjustment of zero point and amplification
- Rescaling of analog output (unit, pressure range)
- Adjustment of low-pass filter
- Selection of instrument address and baud rate

Scope of delivery

Calibration protocol	Mating connector to round plug 423 - 723 - 425 IP40	Mating connector to valve connector, form A, DIN EN 175301-803-A
		

Accessories

Interface converter	Mating connector for round connector, M12 x 1	
		
K-114 <ul style="list-style-type: none"> • Analog measurement 0...10 V and 4...20 mA • 12 V measuring device supply via USB • USB interface electrically isolated • Bias and terminating resistors can be activated 	Connection options <ul style="list-style-type: none"> • E.g. K-114-B with cable outlet instead of screw-type terminals for Binder series 723 (5-pin) • Various adapter cables available 	<ul style="list-style-type: none"> • Angled socket, cable 5 m <i>PN 602515.0093</i> • Angled socket, cable 2 m <i>PN 602515.0094</i> • Female connector, cable 5 m <i>PN 602515.0095</i> • Female connector, cable 2 m <i>PN 602515.0096</i>

For pricing or any further information, please contact Omni Instruments Ltd.