

Fiber Optic to Serial

RS232/485/422 to Multimode Fiber



MCV1-FO-SER

The MCV1-FO-SER is an Industrial Multimode Fiber Optic to Serial converter, that allows to extend the communications up to 2.7 Km And without interferences for electrical noise



MAIN FEATURES

- Industrial DIN rail mountable case
- ST Connectors
- Multimode Fiber Optic Port (TX & RX)
- 1 Serial Port RS232 / RS485 / RS422 (Not simultaneous)

CHARACTERISTICS

- Serial Port: RS232, RS485, RS422 (Not simultaneous)
- Fiber Optic Port: Transmitter & Receptor
- Fiber Optic Connector: ST
- Power Supply: +10/30 Vdc. Power ON LED
- Case: DIN Rail Mountable, Fireproof
- Maximum Distance: 2.7 Km
- Baud rate: Up to 115200 bps
- Fiber Optic supported: Multimode 50/125 um or 62.5/125 um
- Wave Length: 820 nm
- Max. Current: 150mA @ 10V, 75mA @ 30V

ORDERING INFORMATION

MCV1-FO-SER-ST-MU (Multimodo) (Conector ST)

IEC 60950-1:2005+A1

SISTEMA DE GESTIÓN ISO 9001:2015

GESTION DE LA CALIDAD

RI-9000-6174

Acreditado por OAA

For pricing or any further information, please contact Omni Instruments Ltd.



Contact Details:
Tel: +44 1382 443000
Email: info@omni.uk.com

Website: www.omniinstruments.co.uk

Mailing Address: Unit 1, 14 Nobel Road,
Wester Gourdie Industrial Estate,
Dundee, DD2 4UH.