



## TSH202B

### Compact humidity and temperature sensor



### Short description

TSH202B is a compact humidity and temperature 1-wire sensor that offers reliable and accurate data collection. The device integrates basic elements plus signals processing, and provides a fully calibrated digital output.

A unique capacitive element is used for measuring relative humidity while the temperature is measured by a band gap sensor.

Both sensors are seamlessly coupled to a 12-bit analog to digital converter. This results in superior signal quality and fast response time.

### Applications

- Server room and data centers monitoring.
- Environmental quality monitoring and assessment.
- Humidity and temperature monitoring in building management systems.
- Humidity and temperature monitoring for mobile operator facilities, vehicles, greenhouses, etc.

### Technical parameters

Parameter	Value	Units	Remark	Value	Units	Remark
Operating Range	10 to 90*	%RH	non-condensing	-20 to +60*	°C	
Tolerance typ.	±3.0	%RH	20 to 80 %RH	±0.4	°C	-10 to +60°C
Tolerance max.	±5.0	%RH	10 to 90 %RH	±1.0	°C	-20 to +60°C
Long term drift typ.	±0.25**	%RH/year	20 to 80 %RH	±0.05**	°C/year	-10 to +60°C
Resolution	0.1	%RH		0.1	°C	
Power supply/consumption	4.0 to 5.5	VDC		5	mA	
Dimensions	62 x 28 x 16	mm				
Communication	1-Wire					
Cable length	1	m				

\* Recommended operating range is 20% to 80% RH (non-condensing) over -10°C to +60°C.  
Prolonged operation beyond these ranges may result in a shift of sensor reading, with slow recovery time.

\*\* Higher drift values might occur due to contaminant environments with vaporized solvents, out-gassing tapes, adhesives, packaging materials, etc.

For pricing or any further information, please contact Omni Instruments Ltd.



## Usage

Can be used with following **TERACOM** controllers

- TCW241                      - TCW122B-CM                      - TCW122B-WD
- TCW220                      - TCG120-4

## Pinout

Signals	Cable colors	
VDD (+4.0 to +5.5V)	Red	
Data	White	
GND (Ground)	Black	

## Status indicator


The status of the device is shown by single LED, located on the front panel:

- If the LED blinks on period of 1 second, sensors works properly;
- If the LED blinks on period of 3 seconds, there isn't communication with TCWxxx controller;
- If LED doesn't blink, there isn't power supply.

## Wiring example

Ethernet controller TCW122B-CM

TSH202B TSH202B



## 1-Wire Bus

1-Wire is a registered trademark of Maxim Integrated Products, Inc. We strongly recommend read Maxim's 1-Wire tips at <http://www.maxim-ic.com/app-notes/index.mvp/id/148>.

For pricing or any further information, please contact Omni Instruments Ltd.