



MT190

Multi-mode Ultrasonic Thickness Gauge



Product Overview

The MT190 multi-mode ultrasonic thickness gauge is based on ultrasonic measuring principles, allowing it to perform thickness measurements on a wide range of materials, including metals, plastics, ceramics, glass, and other ultrasonic well-conductive materials. It can also measure the sound velocity of objects with known thickness. Compared to traditional methods, this gauge's advantage lies in its ability to complete measurements by contacting only one side of the workpiece. Its unique capability to test thickness through coatings provides an efficient solution for evaluating coated surfaces or corrosion-prone materials without removing the surface coating. Widely used for monitoring corrosion in pipelines and pressure vessels across industries such as petroleum, chemical, metallurgy, shipbuilding, aviation, and aerospace, the MT190 is also effective for accurate measurements of various plates and machined parts. It is an essential precision instrument for enhancing production efficiency and reducing costs.

For pricing or any further information, please contact Omni Instruments Ltd.

Contact Details:

Tel: +44 1382 443000
Email: info@omni.uk.com

Website: www.omniinstruments.co.uk

Mailing Address: Unit 1, 14 Nobel Road,
Wester Gourdie Industrial Estate,
Dundee, DD2 4UH.

Technical Specifications

Technical Specifications	Technical Parameters
	Support two modes for thickness measurement
Measuring Range	Pulse-Echo mode: (0.65 ~ 600)mm Echo-Echo mode: (3 ~ 60)mm
Accuracy	$\pm 0.05\text{mm}$ ($\leq 10\text{mm}$) ; $\pm (0.5\%H + 0.01) \text{mm}$ ($> 10\text{mm}$) ; H refer to the thickness of workpiece
Measurement Frequency	7 times per second for single point measurement, 16 times per second for scan mode measurement.
Display	High contrast Segment LCD display (support for EL backlight display)
Resolution	0.1mm/0.01mm selectable
Sound Velocity Range	(1000 ~ 9999)m/s (Capable for measuring the sound velocity of the object with known thickness)
Probe Calibration	Zero-point calibration, two point calibration
Thickness Measurement Mode	Single Point measurement, min/max measurement, differential measurement Capable for saving and managing 20 groups of thickness data (up to 100 values for each group)
Data Storage	
Units	Metric/Imperial unit selectable
Communication Interface	USB 1.1 interface for connecting with PC for printing
Power Source	With two "AA" size alkaline batteries, it can work above 50 hours continuously with default brightness.
Auto Power Saving	Auto shutdown power saving function
Material	ABS engineering plastic
Size	150mm×74mm×32mm
Weight	245g

Features

- Capable of performing thickness measurements on a wide range of material including metals (such steel, cast iron, aluminum, copper, etc.), plastics, ceramics, composites, epoxies, glass and other ultrasonic well-conductive materials.
- With two thickness measurement modes: Pulse-Echo mode and Echo-Echo mode, it can measure the thickness through the coating without calculating the coating thickness.
- With large storage capacity and lower power design, it can standby super long time above months.
- Capable of measuring the sound velocity of the material, it can meet the thickness testing requirements for various materials.
- Attach with USB data processing software, it can connect with PC for data analysis, storage and printing.
- Capable of compatible with a variety of probes with different frequency and size, it can identify the probe type automatically.
- With probe-zero calibration and two-point calibration functions, it can correct the system error automatically. Equipped with narrow impulse composite high accuracy probe, it has small dead zone and accurate measurement.
- With EL backlight display, it is convenient for using in dim light environments.
- Also equipped with auto sleep, auto shutdown and other power saving functions as well as battery rest capacity indicating function.
- Small, portable, high reliability, it can anti-shock and electromagnetic interference, suitable for harsh operating environments.

For pricing or any further information, please contact Omni Instruments Ltd.

Contact Details:

Tel: +44 1382 443000
Email: info@omni.uk.com

Website: www.omniinstruments.co.uk

Mailing Address: Unit 1, 14 Nobel Road,
Wester Gourdie Industrial Estate,
Dundee, DD2 4UH.

Measuring Principle

The digital ultrasonic thickness gauge determines the thickness of a part or structure by accurately measuring the time required for a short ultrasonic pulse generated by a transducer to travel through the thickness of the material, reflect from the back or inside surface, and be returned to the transducer. The measured two-way transit time is divided by two to account for the down-and-back travel path, and then multiplied by the velocity of sound in the material. The result is expressed in the well-known relationship


$$H = \frac{v \times t}{2}$$

Where:

H - Thickness of the test piece.

v - Sound Velocity in the material.

t - The measured round-trip transit time.



To make sure the probe working properly, it needs to use couplant to isolate the air between the probe surface and the measured workpiece surface. The liquid used for the coupling between the probe and workpiece is called as couplant.

Probe Selection

Model	Freq	Diam	Measuring Range	Lower limit	Description
N05	5MHz	10mm	1.0mm ~ 600mm (in steel)	Φ20mm×3.0mm	Normal Measurement
N05/90°	5MHz	10mm	1.0mm ~ 600mm (in steel)	Φ20mm×3.0mm	Normal Measurement For thin pipe wall or small curvature
N07	7MHz	6mm	0.65mm ~ 200mm (in steel)	Φ15mm×2.0mm	pipe wall measurement
HT5	5MHz	12mm	1mm ~ 600mm (in steel)	30mm	For high temperature (lower than 300°C) measurement.
N02	2.5MHz	14mm	3mm ~ 600mm (in steel) Pulse-Echo: 2mm-600mm (in steel)	20mm	For thick, highly attenuating, or highly scattering materials
P5EE	5MHz	10mm	Echo-Echo: 3mm-100mm (in steel)	Φ20mm×3.0mm	Trough-coating thickness testing



HT5



P5EE



N02



N05



N05/90°



N07

For pricing or any further information, please contact Omni Instruments Ltd.

Configuration

	No.	Type	QTY	Remarks
Standard Configuration	1	Main Unit	1	
	2	Narrow Impulse Thickness Probe (P5EE)	1	
	3	Couplant	1	
	4	ABS Instrument Case	1	
	5	Manual	1	
	6	Warranty Card	1	
	7	Product Certificate	1	
	8	"AA" size alkaline batteries	2	
Optional Configuration	1	Normal Probe N05/90°(5MHz)		
	2	Normal Probe N05 (5MHz)		
	3	High Temperature Probe HT5(5MHz)		
	4	Coarse Grain Probe N02 (2.5MHz)		
	5	Micro Diameter Probe N07 (7MHz)		
	6	High Temperature Couplant		
	7	USB Communication Cable		
	8	Data Proceeding Software		



For pricing or any further information, please contact Omni Instruments Ltd.