

The Squirrel 450/850 series is a cost effective portable data logger with a maximum of 4 or 8 universal inputs.

In common with the Squirrel 1000 series data logger, the 450/850 series is equipped with impressive specifications, long battery life and a three year guarantee. Models 451 and 851 have 4 or 8 universal inputs respectively, configurable for voltage, current and temperature for both thermocouple and thermistor sensors. In addition a serial interface is available for special applications, including Vaisala weather sensor WXT520.

Key Features

- Rugged construction
- Battery or mains operated and easily portable
- Configuration and Metering by:
 - Panel controls and display
 - Locally connected PC (using Darca Software)
 - Remotely connected PC (using Darca Software) or Ethernet adaptor
- Multi language set up menu
- Non volatile internal memory providing up 250,000 readings of secure data, with options to expand to 2,000,000 readings
- Readings can be scaled into appropriate units (e.g. m/sec, p.p.m.)
- Low power consumption for long term unattended use/portable operation
- Clearly labelled connector panel for quick on-site installation
- LAN Network adaptor for Ethernet connection
- Optional Text message on alarm using and /or remote access, external GSM modem

452 / 852



Vaisala weather Sensor



WXT530

Common Features

- Highly accurate: $\pm(0.1\%$ of reading, $+0.2\%$ of range span)
- 12 bit resolution
- Standard internal memory for 250 000 readings
- Sensor power outputs
- External triggers can start and stop the logger
- Environmental: -30 to $+65^{\circ}\text{C}$, 0 to 95°RH non-condensing
- External power supply: 9 to 14V DC (internal battery: 9V)
- Communications via RS232C with auto-baud detect
- Rapid memory download

Optional Features

- Wall bracket
- AC Power supply MP12U ($110/250\text{AC}$) to 12VDC
- Alarms and threshold can be set for all channels
- Internal memory expandable to 2,080,000 readings
- Outdoor enclosure

Accessories

- Moxa D5110AC Serial to Ethernet Converter
- 4G Modem Kit, for SMS
- Comprehensive range of sensors including RH and temperature probe, thermocouple / thermistor probes, current clamps, etc.

*images reproduced with kind permission from Vaisala Ltd. (UK)

Model	Inputs	Features	Application
451 / 851	4 / 8 universal	Each channel configurable for temperature, voltage or current input	
451T / 851T	4 / 8 universal	0.1sec Interval (Fast Recording)	
452 / 852	4 / 8 pulse only	Pulse input only	
453	1 Event + 8 pulse	Plus 1 x pulse and 1 x event input	
451L / 851L	4 / 8 V/C + 1 thermistor	Includes +/- 10mV range, for use with Hukseflux HFP01 heat flux sensor	Solar radiation
451/851 WXT530	4 / 8 universal + 1 serial	As above, plus serial input for Vaisala WXT530 weather sensor* ¹	Weather (inc. solar radiation)

*¹Weather:

The Vaisala weather sensors are:

WXT520 - as WMT52, with rainfall, barometric pressure, RH and temperature.

Vaisala sensors can be powered by the logger batteries/supply. Eltek can supply the Vaisala sensors if required.

* indicates to be ordered separately

System Specification

Logging Modes

Interval / average / event / externally triggered

Log / Scan Interval

1 sec to 24 hours
Optional: 0.1 sec minimum

Analogue Inputs

Accuracy: \pm (0.1% of reading, +0.2% of range span)
Common mode range: 15V
Input Impedance: 1M Ω

Analogue Input Types & Ranges

see tables below

Sensor Excitation

5V / supply voltage - internally selectable

Data memory

Internal memory: 250,000 readings
Option: 2 million readings
Memory modes: stop when full or continuous

Scaling Data

Readings scaled as engineering units

Configuration

Panel controls and display and/or Darca Lite or Darca Plus (PC Software)

Display

2 line, 32-character display for local status monitoring, configuration and stored readings

Communications

RS232 half duplex - 2400 to 38.4K Baud
Modem compatible protocol

Darca Software

Darca Plus for control, download and export, plus graphing and analysis tools

Power supply

Internal: 6 x AA Alkaline batteries
External: 9 to 14 VDC (1.4 watts)
Mains adapter: 12 VDC 6 watts

Battery Life: sampling 8 channels every 5 minutes provides typically 6 months operation

Case

Scratch resistant Nextel coated ABS
width 180mm, height 120mm, depth - see table below

Operating Environment

Temperature range: -30 to 65°C
Humidity: 95% non condensing.
For harsh environments an optional IP67 enclosure is available

Range specification

Each channel can be individually set to any of the following ranges:

Temperature:

Input type	Range °C	Resolution °C
U thermistor	-50 to 150	0.1 (-25 to 100)
(YSI probe input also available)		0.2 (-40 to 125)
K: thermocouple	0 to 900	0.4 (-50 to 100)
	-200 to 450	0.5
T: thermocouple	-200 to 350	0.2

Voltage/Current:

Each V/C channel can be set to any of the 18 voltage or 2 current ranges.

50 μ V Resolution	0.5mV Resolution	5mV Resolution
0 to 50mV	0 to 500mV	0 to 5V
-25 to 25mV	-250 to 250mV	-2.5 to 2.5V
0 to 100mV	0 to 1V	0 to 10V
-50 to 50mV	-500 to 500 mV	-5 to 5V
0 to 200mV	0 to 2V	0 to 20V
-100 to 100mV	-1 to 1V	-10 to 10V

Pulse:

Maximum frequency: 5Hz
Maximum pulses counted per logging interval: 65,000

10mV Hukseflux range	Resolution	Range	Resolution
\pm 10mV	5 μ V	0 to 20mA	10 μ A
		4 to 20mA*	0.05%
		* displayed as 0-100%	



For pricing or any further information, please contact Omni Instruments Ltd.

Contact Details:

Tel: +44 1382 443000
Email: info@omni.uk.com

Website: www.omniinstruments.co.uk

Mailing Address: Unit 1, 14 Nobel Road,
Wester Gourdie Industrial Estate,
Dundee, DD2 4UH.