

SharpEye™ 20/20MI



Mini Triple IR (IR3) Flame Detector

The SharpEye Mini-IR3 Flame Detector (20/20MI) is a high performance and high reliability compact, selfcontained triple spectrum infrared flame detector.

With the highest immunity to false alarms, the Mini-IR3 has applications in a wide range of industrial and commercial facilities, where the threat of accidental fire involves hydrocarbon fuels such as gasoline, kerosene, diesel fuel, aviation jet fuels like JP-4, JP-5, JP-8, hydraulic fluids, paints and solvents, monomers and polymers like ethylene and polyethylene, natural gas (LNG), town gas and liquefied petroleum gas (LPG), hydrocarbon gases like methane, ethane, propane, butane, acetylene, propylene, etc.

The patented Triple IR design also offers 3-4 times the detection distance of any conventional IR or UV/IR Detector.

This detector is packaged in a compact, lightweight housing for easy installation and where space is at a premium. It is specially designed as a generalpurpose flame detector for industrial applications to withstand "harsb" environmental conditions, including extreme temperatures, high humidity, vibrations, etc.

MAIN FEATURES

- Triple Spectrum Design
- 80% Less Power Consumption
- Highly Immune to False Alarms
- Large Field of View (100° horizontal/vertical)
- Sensitivity Selection
- User-Programmable Functions
- Configurable via software from a PC or handheld device
- Automatic and Manual Built-In-Test (BIT)
- Standard 4-Wire Connection
- 4-20mA sink or source (3-4 wires) configuration
- RS-485 Modbus Compatible
- MTBF Minimum 100,000 Hours
- 3-Year Warranty
- FM Approval (Functional)
- EN54-10 (VdS) Approved for 20/20MI-1

APPLICATIONS

- Aircraft-hangars and maintenance areas including landing gear pits
- Automotive parts manufacturing
- Car parking towers and garages
- Chemical industry
- Mining and heavy-duty vehicles
- Nuclear power plants
- Paint spray booths
- Petrochemical facilities
- Power generation - pumps, generators, and unmanned stations
- Printing-presses and facilities
- Recreational and sports arenas (facilities)
- Storage areas
- Tank farms with fixed or floating roofs
- Wet bench manufacturing

For pricing or any further information, please contact Omni Instruments Ltd.



Measurement and data acquisition solutions

Contact Details:

Tel: +44 1382 443000

Email: info@omni.uk.com

Website: www.omniinstruments.co.uk

Mailing Address: Unit 1, 14 Nobel Road,
Wester Gourdie Industrial Estate,
Dundee, DD2 4UH.

GENERAL SPECIFICATIONS

Spectral Response	Three IR Bands					
Detection Range (Highest Sensitivity Setting for 1 ft ² (0.1m ²) pan fire)		ft	m		ft	m
	Gasoline	133	40	IPA (Isopropyl Alcohol)	100	30
	n-Heptane	133	40	Methanol	100	30
	Diesel Fuel	90	27	Methane*	40	12
	JP5	100	30	LPG (Propane)*	40	12
	Kerosene	100	30	Polypropylene Pellets	16	5
	Alcohol (Ethanol)	100	30	Office Paper	50	15
	*20" (0.5m) long 8" (0.2m) width plume fire					
Response Time	Typical 5 sec.					
Adjustable Time Delay	Up to 30 sec.					
Sensitive Range	4 Sensitive Ranges for 1 ft ² (0.1m ²) gasoline pan fire: 20/20MI-1: 33 ft (10m) to 133 ft (40m) 20/20MI-3: 7.5 ft (2.5m) to 33 ft (10m)					
Field of View	100° horizontal, 100° vertical					
Built-in-Test	Manual and Automatic BIT					
Temperature Range	Operating: -40°F (-40°C) to 160°F (70°C) Storage: -65°F (-55°C) to 185°F (85°C)					
Humidity	Up to 95%					

ELECTRICAL SPECIFICATIONS

Power Supply	Operating Voltage: 18-32 VDC
Power consumption	Max. 25 mA in stand-by Max. 50 mA in alarm
Electrical Connection	12 wires 6 ft. (2m) cable (for junction box connection) Optional: 12-wires electrical connector (the suitable connector will be supplied)
Electrical Input Protection	According to MIL-STD-1275B
Electromagnetic Compatibility	EMI/RFI protected CE Marked

OUTPUTS

Relays	Alarm and Fault SPST volt-free contacts rated 2A at 30 VDC Fault relay normally closed, Alarm Relay normally open
4-20mA	Sink (source option) configuration Fault: 0 ±0.5mA BIT Fault: 2mA ±10% Normal: 5mA ±10% Warning: 10mA ±5% Alarm: 15mA ±5% Resistance Loop: 100-600 Ω
RS-485	The detector is equipped with an RS-485 communication link that can be used in installation with computerized controllers. The RS-485 is Modbus compatible

MECHANICAL SPECIFICATIONS

Dimensions	4" x 4" x 2.5" (100 x 100 x 62 mm)
Weight	St.St 316L 2.5Lb (1.2 Kg) Tilt Mount 0.8Lb (0.37 Kg)
Enclosure	Stainless Steel 316L with electro polish finish
Environmental Standards	Meets MIL-STD-810C for Humidity, Salt & Fog, Vibration, Mechanical Shock, High Temp, Low Temp
Water and Dust	IP66 and IP67 per EN60529 NEMA 250 6P

APPROVALS

FM (Functionality)
EN54-10 (VdS) - 20/20MI-1 Only

ACCESSORIES

Flame Simulator	FS-1100	Air Shield	20/20-787
Tilt Mount	20/20-005	Laser Pointer	787969
Rain Shield	787980	Hand Held Pocket PC Diagnostic Kit	777820

For pricing or any further information, please contact Omni Instruments Ltd.



Measurement and data acquisition solutions

Contact Details:
Tel: +44 1382 443000
Email: info@omni.uk.com

Website: www.omniinstruments.co.uk

Mailing Address: Unit 1, 14 Nobel Road,
Wester Gourdie Industrial Estate,
Dundee, DD2 4UH.